



## Status of U.L. approvals, Product Certified for Canada included

LATI S.p.A. - updated - March 2008

file LATI: E 54080 - QMFZ2 , QMFZ8

### UL FOOTNOTES

- |   |  |
|---|--|
| <p>(a) indicates glass loadings from 1-30 percent</p> <p>(b) indicates glass loadings from 6-34 percent</p> <p>(c) indicates glass loadings from 5-30 percent</p> <p>(d) indicates glass loadings from 1-29 percent</p> <p>(e) indicates glass loadings from 20-40 percent</p> <p>(f2) Subjected to one or more of the following tests: Ultraviolet Light, Water Exposure or Immersion in accordance with UL 746C, where the acceptability for outdoor use is to be determined by UL Inc.</p> <p>(g) indicates glass loadings from 26-49 percent</p> <p>(h) indicates glass loadings from 16-34 percent</p> <p>(i) indicates glass loadings from 10-30 percent</p> <p>(k) indicates glass loadings from 20-30 percent</p> | <p>(l) indicates glass loadings from 16-29 percent</p> <p>(m) indicates glass loadings from 16-24 percent</p> <p>(n) indicates glass loadings from 26-34 percent</p> <p>(p) indicates glass loadings from 36-49 percent</p> <p>(s) indicates glass loadings from 11-49 percent</p> <p>(q) Optional marking consisting of a generic indication of color (English or Italian) followed by an alphanumeric code (consisting of 4 digits and 1 letter) indicating color shade.</p> <p>(r) Optional marking consisting of an alphanumeric code (consisting of 1 or 2 letters followed by one number) referring to manufacturing process information.</p> <p>(u) recognition valid up to 50% regrind</p> <p>(@) all color except black</p> |
|---|--|



(1-30) indicates MFI from 1-30 g/10'

LATI Products listed in UL file E54080 meet US and Canadian requirements.

Product	Material	Colors	Min Thk mm	UL 94 Flame Class	R.T.I.										
					Elec			Mech			H	D	G	G	
					With Imp	w/o Imp		H W	H A	V T	4 9	C T	W I	W F	
PA66	Latamid 66 (q) (r)	ALL	0.75	V-2	65	65	65	-	-	-	-	-	-	-	-
	Latamid 66 PX15 (q) (r)	BK	0.86	HB	65	65	65	-	-	-	-	-	-	-	-
	Latamid 66 H2 G/25 (q) (r)	ALL	0.75	HB	105	80	100	4	0	-	-	-	-	-	-
			3.00	HB	105	80	110	1	0	1	6	1	-	-	-
	Latamid 66 H2 G/(g) (q) (r) (see notes)	ALL	0.75	HB	105	80	100	4	0	-	-	-	-	-	-
			3.00	HB	105	80	105	1	0	1	6	1	-	-	-
	Latamid 66 H2 G/30 (q) (r)	ALL	0.75	HB	105	80	100	4	0	-	-	-	-	-	-
			3.00	HB	105	80	105	1	0	1	6	1	-	-	-
	Latamid 66 H2 G/50 (q) (r)	ALL	0.75	HB	105	85	100	3	0	-	-	-	-	-	-
			3.00	HB	105	85	105	1	0	0	6	0	-	-	-
	Latamid 66 H2 G/60 (q) (r)	BK	0.75	HB	65	65	65	-	-	-	-	-	-	-	-
			0.75	HB	130	110	130	3	0	-	-	-	-	-	-
	Latamid 66 VH2 G/15 (q) (r)	NC,BK	1.50	HB	130	120	130	2	0	-	-	-	-	-	-
			3.00	HB	130	120	130	0	0	1	6	2	-	-	-
	Latamid 66 VH2 G/(m) (q) (r) (see notes)	NC,BK	0.75	HB	115	90	120	4	0	-	-	-	-	-	-
			1.50	HB	120	95	120	2	0	-	-	-	-	-	-
	Latamid 66 VH2 G/25 (q) (r)	NC,BK	3.00	HB	125	95	125	0	0	0	6	2	-	-	-
			0.71	HB	115	90	120	4	0	-	-	-	-	-	-
	Latamid 66 VH2 G/(n) (q) (r) (see notes)	NC,BK	1.50	HB	120	95	120	2	0	-	-	-	-	-	-
			3.00	HB	125	95	125	0	0	0	6	2	-	-	-
	Latamid 66 VH2 G/30 (q) (r)	ALL	0.71	HB	115	90	120	4	0	-	-	-	-	-	-
			1.50	HB	120	95	120	2	0	-	-	-	-	-	-
	Latamid 66 VH2 G/35 (q) (r)	NC,BK	3.00	HB	125	95	125	0	0	0	6	2	-	-	-
			0.71	HB	115	115	120	4	0	-	-	-	-	-	-
	Latamid 66 VH2 G/(p) (q) (r) (see notes)	NC,BK	1.50	HB	120	120	120	1	0	-	-	-	-	-	-
			3.00	HB	125	120	125	0	0	0	6	1	-	-	-
	Latamid 66 VH2 G/50 (q) (r)	NC,BK	0.71	HB	115	120	120	4	0	-	-	-	-	-	-
			1.50	HB	120	120	120	0	0	-	-	-	-	-	-
	Latamid 66 S/30 (q) (r)	ALL	3.00	HB	125	120	125	0	0	0	6	1	-	-	-
			0.75	HB	65	65	65	-	-	-	-	-	-	-	-


Product	Material	Colors	R.T.I.														
			Min Thk mm	UL 94 Flame Class	Elec			Mech			H W I	H A I	H V T R	D 4 9 5	C T I	G W I T	G W I F I
					With Imp	w/o Imp	Imp	With Imp	w/o Imp	Imp							
Kelon A H CE/40 (q) (r)	ALL	0.71	HB	120	95	120	4	0	-	-	-	-	-	-	-	-	
		1.50	HB	120	95	120	2	0	-	-	-	-	-	-	-	-	
		3.00	HB	125	95	125	3	0	3	6	1	-	-	-	-	-	
Latamid 66 H-V0 (q) (r)	NC	0.41	V-0	65	65	65	-	-	-	-	-	-	-	-	-	-	
		0.81	V-0	125	75	75	4	0	-	-	-	-	-	-	-	-	
		1.50	V-0	125	75	75	3	0	-	-	-	-	-	-	-	-	
Latamid 66 H2PX30-V0 (q) (r)	ALL	0.41	V-0	65	65	65	-	-	-	-	-	-	-	-	-	-	
		0.71	V-0	65	65	65	-	-	-	-	-	-	-	-	-	-	
		0.40	V-2	65	65	65	-	-	-	-	-	-	-	-	-	-	
Latamid 66 H2PX-V0 (q) (r)	ALL	0.75	V-0	65	65	65	4	0	-	-	-	-	-	-	-	-	
		0.75	V-1	65	65	65	4	0	-	-	-	-	-	-	-	-	
		1.00	V-0	65	65	65	4	0	-	-	-	-	-	775	960		
Latamid 66 BH-V0 (q) (r)	ALL	0.75	V-0	65	65	65	-	-	-	-	-	-	-	-	-	-	
		0.75	V-2	65	65	65	-	-	-	-	-	-	-	-	-	-	
		1.00	V-2	65	65	65	-	-	-	-	-	-	-	850	850		
Latamid 66 H2PX-V2 (q) (r)	ALL	2.00	V-2	65	65	65	-	-	-	-	-	-	-	850	960		
		3.00	V-2	65	65	65	-	-	-	-	-	-	-	850	960		
		0.75	V-0	65	65	65	-	-	-	-	-	-	-	-	-		
Latamid 66 BG/20-V (q) (r)	ALL	1.50	V-1	65	65	65	-	-	-	-	-	-	-	-	-		
		3.00	V-0	65	65	65	-	-	-	-	-	-	-	-	-		
		0.81	V-0	110	80	95	4	0	-	-	-	-	-	-	-		
Latamid 66 H2 G/05-V0 (q) (r)	ALL	1.50	V-0	110	80	100	2	0	-	-	-	-	-	-	-		
		3.00	V-0	110	80	105	1	0	1	6	2	-	-	-			
		0.81	V-0	110	80	95	4	-	-	-	-	-	-	-	-		
Latamid 66 H2 G/(b)-V0 (q) (r) (see notes)	ALL	1.50	V-0	110	80	100	2	0	-	-	-	-	-	-			
		3.00	V-0	110	80	105	1	0	1	6	2	-	-	-			
		0.81	V-0	110	85	110	4	0	-	-	-	-	-	-			
Latamid 66 H2 G/25-V0 (q) (r)	ALL	1.50	V-0	110	85	110	2	0	-	-	-	-	-	-			
		3.00	V-0	110	85	110	1	0	1	6	2	-	-	-			
		0.81	V-0	115	105	110	0	1	-	-	-	-	-	-			
Latamid 66 H2 G/35-V0 (q) (r)	ALL	1.50	V-0	115	105	120	0	0	-	-	-	-	-	-			
		3.00	V-0	115	105	120	0	0	1	6	2	-	-	-			
		0.75	V-0	100	75	75	3	0	-	-	-	-	-	-			
Latamid 66 H2 G/25-V0KB (q) (r)	NC,BK	1.50	V-0	100	80	80	1	0	-	-	-	-	-	-			
		3.00	V-0	100	85	85	1	0	1	6	1	-	-	-			
		0.75	V-0	105	75	75	3	0	-	-	-	-	-	-			
Latamid 66 H2 G/35-V0KB (q) (r)	NC,BK	1.50	V-0	105	85	85	1	0	-	-	-	-	-	-			
		3.00	V-0	105	85	85	1	0	1	6	1	-	-	-			
		0.75	HB	105	75	75	2	0	-	-	-	-	-	-			
Latamid 66 H2 G/15-V0KB1 (q) (r)	ALL	1.50	V-0	105	75	75	1	0	-	-	-	-	-	-			
		3.00	V-0	105	85	85	0	0	1	6	1	-	-	-			
		0.75	HB	130	115	140	3	0	-	-	-	-	-	-			
Latamid 66 H2 G/(h)-V0KB1 (q) (r) (see notes)	ALL	1.50	V-0	130	115	140	1	0	-	-	-	-	-	-			
		3.00	V-0	130	115	140	0	0	1	6	1	-	-	-			
		0.75	HB	130	115	150	3	0	-	-	-	-	-	-			
Latamid 66 H2 G/35-V0KB1 (q) (r)	ALL	1.50	V-0	130	115	150	1	0	-	-	-	-	-	-			
		3.00	V-0	130	115	150	0	0	1	6	0	-	-	-			
		0.86	V-0	110	100	115	0	1	-	-	-	-	-	-			
Latamid 66 H2 G/50-V0KB1 (q) (r)	NC,BK	1.00	V-0	110	105	120	0	1	-	-	-	-	800	960			
		1.50	V-0	110	105	120	0	1	-	-	-	-	800	960			
		2.00	V-0	110	105	120	0	1	-	-	-	-	800	960			
Latamid 66 H2 G/25-V0KB3 (q) (r)	NC,BK,GY	3.00	V-0	110	110	120	0	0	1	5	0	-	-	-			
		1.50	V-0	130	115	140	0	0	-	-	-	-	-	-			
		3.00	V-0	130	115	140	0	0	0	5	0	-	-	-			
Latamid 66 H2 G/35-V0KB3 (q) (r)	NC,BK	0.75	V-0	65	65	65	0	0	-	-	-	-	-	-			
		1.00	V-0	65	65	65	0	0	-	-	-	-	775	960			
		2.00	V-0	65	65	65	0	0	-	-	-	-	800	960			
Latamid 66 H2 G/25-V0KB4 (q) (r)	NC,BK,GY,GN	3.00	V-0	65	65	65	0	0	-	-	0	800	960				
		NC	0.40	V-2	65	65	65	-	-	-	-	-	-	-			
		NC, BK	0.50	V-2	130	65	65	0	0	-	-	-	-	-			
Latamid 66 H2 G/25-V0CT1 (q) (r)	ALL	0.71	V-0	140	120	130	0	0	-	-	-	-	850	960			
		1.50	V-0	140	120	130	0	0	-	-	-	-	850	960			
		2.00	V-0	140	120	130	0	0	-	-	-	-	900	960			
Latamid 66 H2 G/25-V0HF1 (q) (r)	ALL	3.00	V-0	140	120	130	0	0	1	6	1	900	960				
		0.50	HB	65	65	65	-	-	-	-	-	-	-	-			
		0.71	V-0	65	65	65	0	0	-	-	-	-	-	-			
Latamid 66 H2 G/25-V0HF (q) (r)	ALL	1.50	V-0	65	65	65	0	0	-	-	-	-	775	960			
		3.00	V-0	65	65	65	0	0	1	6	0	800	960				
		0.75	V-0	65	65	65	-	-	-	-	-	-	-	-			
Latamid 66 H2 G/20-V2 (q) (r)	ALL	0.75	V-2	65	65	65	-	-	-	-	-	-	-	-			
		1.00	V-2	65	65	65	-	-	-	-	-	-	800	960			
		2.00	V-2	65	65	65	-	-	-	-	-	-	900	960			
Kelon A FR H2 CEG/250-V0 (q) (r)	ALL	3.00	V-2	65	65	65	-	-	-	-	-	-	900	960			
		0.74	HB	65	65	65	-	-	-	-	-	-	-	-			
		1.50	V-0	65	65	65	-	-	-	-	-	-	-	-			
Kelon A FR H2 CETG/300-V0 (q) (r)	ALL	0.74	V-0	130	100	120	0	0	-	-	-	-	-	-			
		1.00	V-0	130	100	120	0	0	-	-	-	-	850	960			
		1.10	V-0	130	100	120	0	0	-	-	-	-	-	-			
Kelon A FR H2 CET/35-V2 (q) (r)	ALL	1.50	V-0	130	100	130	0	0	-	-	-	-	850	960			
		3.00	V-0	130	100	130	0	0	2	6	2	900	960				
		0.71	V-2	140	100	140	0	0	-	-	-	-	-	-			
Kelon A FR H2 CER/25-V2HF (q) (r)	ALL	1.50	V-2	140	100	140	0	0	-	-	-	-	800	960			
		3.00	V-2	140	105	140	0	0	0	5	1	825	960				
		0.80	V-2	65	65	65	-	-	-	-	-	-	-	-			
PA66/6 Latamid 68 H2-V0 (q) (r)	ALL	0.41	V-0	65	65	65	4	0	-	-	-	-	-	-			
		0.71	V-0	140	95	110	4	0	-	-	-	-	-	-			
		1.50	V-0	140	95	110	4	0	-	-	-	-	960	960			
		3.00	V-0	140	95	110	3	0	-	-	-	-	-	-			

Product	Material	Colors	Min Thk mm	UL 94 Flame Class	R.T.I.										
					Elec		Mech		H W	H A	H V	D 4	C T	G W	G W
					With Imp	w/o Imp	I	I							
	Latamid 68 H2-V0H (q) (r)	RD,BK	0.75 1.50 2.00 3.00	V-0 V-0 V-0,5VA V-0,5VA	130 130 130 130	105 105 105 105	130 130 130 130	4 3 3 1	0 0 0 0	- - - 1	- - - 6	- - - 3	- - - -	- - - -	
PA6	Latamid 6 (q) (r)	NC,BK	0.75 1.50 3.00	V-2 V-2 V-2	65 140 140	65 90 95	65 115 115	- 4 3	- 0 0	- - 0	- - 5	- - 0	- - -	- - -	
	Latamid 6 BH (q) (r)	ALL	0.75 1.50 3.00	HB V-2 V-2	130 140 140	115 95 95	140 115 115	4 4 3	0 0 0	- - 0	- - 5	- - 0	- - -	- - -	
	Latamid 6 H2 G/10 (q) (r)	ALL	0.75 1.50 3.00	HB HB HB	130 130 130	115 115 130	140 140 155	4 4 4	0 0 0	- - -	- - 5	- - 1	- - -	- - -	
	Latamid 6 H2 G/30 (q) (r)	ALL	0.71 0.75 1.50 3.00	HB HB HB HB	65 125 125 125	65 115 115 125	65 140 140 155	- - 4 4	- - 0 0	- - -	- - 0	- - 5	- - 1	- - -	
	Latamid 6 H2 G/(s) (q) (r)	ALL	0.75 1.50 3.00	HB HB HB	125 125 125	115 115 125	140 140 155	4 4 4	0 0 0	- - 0	- - 5	- - 1	- - -	- - -	
	Latamid 6 H2 G/50 (q) (r)	ALL	0.75 1.50 3.00	HB HB HB	125 125 125	120 120 125	150 150 155	4 4 4	0 0 0	- - 0	- - 5	- - 0	- - -	- - -	
	Kelon B H CET/30 (q) (r)	ALL	0.71 1.50 3.00	HB HB HB	140 140 140	105 105 105	140 140 140	4 - 3	0 - 0	- - 0	- - 6	- - 1	- - -	- - -	
	Kelon B H CETG/300 (q) (r)	ALL	1.50	HB	65	65	65	-	-	-	-	-	-	-	
	Latamid 6 H2 PX-V0 (q) (r)	NC	0.70 1.00 2.00 3.00	V-0 V-0 V-0 V-0	65 65 65 65	65 65 65 65	65 65 65 65	- - - -	- - - -	- - - -	- - - -	- - - -	800 800 800	960 960 960	
	Latamid 6 H-V0 (q) (r)	ALL	0.40 0.86 1.50 3.00	V-2 V-0 V-0 V-0	65 140 140 140	65 105 105 105	65 120 120 120	4 2 2	0 0 0	- - -	- - 0	- - 6	- - 0	- - -	
	Latamid 6 H2 PX-V2 (q) (r)	NC	0.75 1.00 2.00 3.00	V-2 V-2 V-2 V-2	65 65 65 65	65 65 65 65	65 65 65 65	- - - -	- - - -	- - - -	- - - -	- - - -	825 825 825	850 900 900	
	Latamid 6 G/20-V1 (q) (r)	ALL	1.50 3.00	V-1 V-0	65 65	65 65	65 65	- -	- -	- -	- -	- -	- -	- -	
	Latamid 6G/(k)-V1 (q) (r) (see notes)	ALL	1.50 3.00	V-1 V-0	65 65	65 65	65 65	- -	- -	- -	- -	- -	- -	- -	
	Latamid 6 G/30-V1 (q) (r)	ALL	1.50 3.00	V-1 V-0	65 65	65 65	65 65	- -	- -	- -	- -	- -	- -	- -	
	Latamid 6 H2 G/15-V0 (q) (r)	ALL	1.50	V-0	65	65	65	-	-	-	-	-	-	-	
	Latamid 6 H2 G/(l)-V0 (q) (r) (see notes)	ALL	1.50	V-0	65	65	65	-	-	-	-	-	-	-	
	Latamid 6 H2 G/30-V0 (q) (r)	ALL	1.50	V-0	65	65	65	-	-	-	-	-	-	-	
	Latamid 6 H2 G/20-V2HF (f2) (q) (r)	ALL	0.75 1.50 3.00	V-2 V-2 V-2	120 120 120	115 120 120	115 120 120	2 2 2	0 0 0	- - 1	- - 6	- - 1	- - -	- - -	
	Latamid 6 H2 G/(k)-V2HF (q) (r)	ALL	0.75 1.5 3.0	V-2 V-2 V-2	130 120 120	120 120 120	120 120 120	2 2 2	0 0 0	- - 1	- - 6	- - 1	- - -	- - -	
	Latamid 6 H2 G/30-V2HF (q) (r)	ALL	0.75 1.5 3.0	V-2 V-2 V-2	130 130 130	120 120 130	120 130 130	2 1 0	0 0 0	- - 1	- - 6	- - 1	- - -	- - -	
	Latamid 6 H2 G/30-V0CT1 (q) (r)	ALL	0.75 1.50 3.00	V-0 V-0 V-0	130 130 130	115 115 115	130 130 130	0 0 0	0 0 0	- - 1	- - 5	- - 1	- - -	- - -	
	Latamid 6 H2 G/30-V0HF1 (q) (r)	ALL	0.75 1.00 2.00 3.00	V-0 V-0 V-0 V-0	65 65 65 65	65 65 65 65	65 65 65 65	- - - -	- - - -	- - - -	- - - -	- - - 0	775 775 775	960 960 960	
	Kelon B FR H CET/05-V2HF (q) (r)	ALL	0.71	V-2	65	65	65	-	-	-	-	-	-	-	
	Kelon B FR H CET/30-V0 (q) (r)	ALL	0.71 1.50 3.00	V-2 V-0 V-0	140 140 140	105 105 105	140 140 140	0 0 0	0 0 0	- - 0	- - 6	- - 1	- - -	- - -	
	Kelon B FR H CETG/250-V0 (q) (r)	ALL	0.75 1.50 3.00	V-0 V-0 V-0	140 140 140	120 120 140	140 140 140	0 0 0	0 0 0	- - 0	- - 6	- - 2	- - -	- - -	
	Kelon B FR H2 CEG/500-V0CT3 (q) (r)	ALL	0.75 1.20 3.00	V-1 V-0 V-0	150 150 150	105 110 120	130 140 140	- 0 0	- 0 0	- - -	- - -	- - 0	- - -	- - -	
	Kelon B FR H2 CE/25-V2HF (q) (r)	ALL	0.70	V-2	65	65	65	-	-	-	-	-	-	-	
PP	Latene AG7H G/30 (q) (r)	ALL	1.50	HB	65	65	65	-	-	-	-	-	-	-	
	Latene AG20H G/40 (q) (r)	ALL	0.75	HB	65	65	65	-	-	-	-	-	-	-	
	Latene 9H TES/30 (q) (r)	ALL	1.50	HB	65	65	65	-	-	-	-	-	-	-	
	Latene 7H2W TR/40 (q) (r)	ALL	1.5-2.7	HB	65	65	65	-	-	-	-	-	-	-	
	Latene 7 T/40 (q) (r)	GY	1.5-2.7	HB	65	65	65	-	-	-	-	-	-	-	
	Latene 22H2 MX/25 (q) (r)	ALL	1.50 3.00	HB HB	65 65	65 65	65 65	- -	- -	- -	- -	- -	- -	- -	
	Latene 9-V0 FE66 (q) (r)	NC,(BN)	1.80	V-0	65	65	65	-	-	-	-	-	-	-	
	Latene 7 TR-V2 (q) (r)	ALL	0.75	V-2	65	65	65	-	-	-	-	-	-	-	

Product Material		Colors	R.T.I.												
			Min Thk mm	UL 94 Flame Class	Elec		Mech		H W I	H A I	H V T R	D 4 9 5	C T I	G W I	G W I
					65	65	65	65							
Latene 7-V2 (q) (r)	ALL	1.50	V-2	65	65	65	-	-	-	-	-	-	-	-	
		3.00	V-2	65	65	65	-	-	-	-	-	-	-	-	
Latene 7 H2-V2HF	ALL	0.75	V-2	65	65	65	-	-	-	-	0	-	-	-	
		1.00	V-2	65	65	65	-	-	-	-	-	775	960		
		2.00	V-2	65	65	65	-	-	-	-	-	775	960		
Latene 7H2W-V0 (q) (r)	NC, BK	2.10	V-2	65	65	65	-	-	-	-	-	-	-		
		NC	0.55	V-2	65	65	65	4	0	-	-	-	-		
		BK	0.45	V-2	65	65	65	4	0	-	-	-	-		
		NC, BK	1.00	V-2	65	65	65	4	0	-	-	-	825	960	
Latene 1H2W-V0 (q) (r)	ALL	1.50	V-0	110	115	115	2	0	-	-	-	-	-		
		3.00	V-0	110	115	115	1	0	1	6	0	-	-		
		1.50	V-0	110	115	115	2	0	-	-	-	-	-		
Latene (1-30)H2W-V0 (q) (r) (see notes)	ALL	3.00	V-0	110	115	115	1	0	1	6	0	-	-		
		1.50	V-0	110	115	115	2	0	-	-	-	-	-		
Latene 30H2W-V0 (q) (r)	ALL	3.00	V-0	110	115	115	1	0	1	6	0	-	-		
		0.75	V-0	100	100	100	3	0	1	-	-	-	-		
Latene 7H2W T-V0 (q) (r)	WT, GY	1.50	V-0	100	100	100	3	0	1	-	-	-	-		
		3.00	V-0	100	100	100	2	0	1	6	0	-	-		
		2.00	5VA	100	100	100	3	0	-	-	-	-	-		
Latene 7H2W T-V0E (q) (r)	ALL	0.75	V-0	65	65	65	4	2	-	-	-	-	-		
		1.5	V-0	65	65	65	3	0	-	-	-	-			
		2.00	V-0,5VB	65	65	65	3	0	-	-	-	-			
		3.00	V-0,5VB	65	65	65	2	0	-	-	-	-			
Latene 7 T-V0 (q) (r)	NC	1.50	V-0	65	65	65	-	-	-	-	-	-			
		3.00	V-0	65	65	65	-	-	-	-	-	-			
Latene 7 G/25-V0 (q) (r)	NC	1.50	V-0	65	65	65	-	-	-	-	-	-			
Latene AG3H2W G/30-V0 (q) (r)	ALL	0.89	V-0	65	65	65	-	-	-	-	-	-			
Latene AG3H2W G/30-V0(f2) (q) (r)	BK	3.0	-	65	65	65	-	-	-	-	-	-			
Latene AG7H2 G/30-V0HF (q) (r)	BK	1.50	V-0	65	65	65	-	-	-	-	-	-			
Latene EP 7-V2 (q) (r)	ALL	1.50	V-2	65	65	65	-	-	-	-	-	-			
Latene EP 3H-V0 (q) (r)	YL	1.50	V-0	65	65	65	-	-	-	-	-	-			
<b>ABS</b>	<b>Lastilac SP G/05 (q) (r)</b>	ALL	1.50	HB	60	60	60	-	-	-	-	-	-		
	Lastilac SP G/ (c) (q) (r) (see notes)	ALL	1.50	HB	60	60	60	-	-	-	-	-	-		
	Lastilac SP G/30 (q) (r)	ALL	1.50	HB	60	60	60	-	-	-	-	-	-		
	Lastilac RT-HB (q) (r)	ALL	1.50	HB	60	60	60	-	-	-	-	-	-		
	Lastilac RT S/20 (q) (r)	ALL	1.50	HB	60	60	60	-	-	-	-	-	-		
	Lastilac AR-V0 (q) (r)	3.00	HB	60	60	60	-	-	-	-	-	-			
		1.50	V-0	60	60	60	-	-	-	-	-	-			
	Lastilac AR-V0E (q) (r)	3.30	5VA	60	60	60	-	-	-	-	-	-			
		1.50	V-0	60	60	60	-	-	-	-	-	-			
	Lastilac ARUV-V0 (q) (r)	3.00	V-0	60	60	60	-	-	-	-	-	-			
		1.70	V-0	60	60	60	3	0	-	-	-	-			
	Lastilac TR1-V0 (q) (r)	ALL	3.30	5VA	60	60	60	2	0	3	6	1	-		
	Lastilac TR G/(d)-V0 (q) (r) (see notes)	NC	1.70	V-0	60	60	60	-	-	-	-	-	-		
	Lastilac AR G/30-V0 (q) (r)	ALL	1.50	V-0	60	60	60	-	-	-	-	-	-		
<b>Alloys</b>	<b>Lastilac 11 G/10 (q) (r)</b>	NC	1.50	HB	60	60	60	-	-	-	-	-	-		
	Lastiflex AR-V0 (q) (r)	ALL	0.71	V-0	50	50	50	-	-	-	-	-	-		
		3.00	5VA	50	50	50	-	-	-	-	-	-			
<b>PS</b>	<b>Lastirol R-V0 (q) (r)</b>	NC	1.60	V-2	50	50	50	-	-	-	-	-	-		
	Lastirol R-V2 (q) (r)	NC	3.00	V-0	50	50	50	-	-	-	-	-	-		
		1.60	V-2	50	50	50	-	-	-	-	-	-			
	Lastirol TR G/10-V1 ES (q) (r)	NC	3.00	V-2	50	50	50	-	-	-	-	-	-		
	Lastirol TR G/10-HB ES (q) (r)	NC, BK	6.00	V-1	50	50	50	-	-	-	-	-	-		
<b>PPOm</b>	<b>Laril 13-V1 (q) (r)</b>	NC, BK	1.50	V-1	50	50	50	-	-	-	-	-	-		
	Laril 13-V1KC (q) (r)	GY	1.50	V-1	50	50	50	-	-	-	-	-	-		
		6.00	V-0	50	50	50	-	-	-	-	-	-			
	Laril 13 G/(a)-V1 (q) (r) (see notes)	NC	1.50	V-1	50	50	50	-	-	-	-	-	-		
		6.00	V-0	50	50	50	-	-	-	-	-	-			
	Laril 13 G/20-V1 (q) (r)	GY, NC, BK	1.50	V-1	50	50	50	-	-	-	-	-	-		
		NC	6.00	V-0	50	50	50	-	-	-	-	-			
<b>PC</b>	<b>Latilon 24D-V2 (q) (r)</b>	ALL	1.0	V-2	80	80	80	-	-	-	-	-	-		
	Latilon 26D-V2 (q) (r)	ALL	2.5	V-2	80	80	80	-	-	-	-	-	-		
		1.0	V-2	80	80	80	-	-	-	-	-	-			
	Latilon 28D-V2 (q) (r)	ALL	2.5	V-2	80	80	80	-	-	-	-	-	-		
		1.0	V-2	80	80	80	-	-	-	-	-	-			
	Latilon 30D-V2 (q) (r)	ALL	2.5	V-2	80	80	80	-	-	-	-	-	-		
		1.0	V-2	80	80	80	-	-	-	-	-	-			
	Latilon 28-V0 (q) (r)	ALL	0.89	V-2	80	80	80	-	-	-	-	-	-		
		3.00	V-0	80	80	80	-	-	-	-	-	-			

Product	Material	Colors	Min Thk mm	UL 94 Flame Class	R.T.I.										
					Elec					Mech					
					With Imp	w/o Imp	H W I	H A I	H V T R	D 4 9 5	C T I	G W I T	G W F I		
	Latilon 28D-V0 (q) (r)	ALL	0.89 3.00	V-2 V-0	80 80	80 80	80 80	- -	- -	- -	- -	- -	- -	- -	- -
	Latilon 30-V0 (q) (r)	NC	0.91 1.70	V-2 V-0	80 80	80 80	80 80	- -	- -	- -	- -	- -	- -	- -	- -
	Latilon 30D-V0 (q) (r)	NC	0.91 1.70	V-2 V-0	80 80	80 80	80 80	- -	- -	- -	- -	- -	- -	- -	- -
	Latilon 28D G/(e) (q) (r) (see notes)	ALL	1.50 6.00	V-1 V-0	80 80	80 80	80 80	- -	- -	- -	- -	- -	- -	- -	- -
	Latilon 30D G/10-V0 (q) (r)	ALL	0.89 1.70	V-2 V-0	80 80	80 80	80 80	- -	- -	- -	- -	- -	- -	- -	- -
	Latilon 28D G/20-V0	GN	0.60	HB	80	80	80	-	-	-	-	-	-	-	-
		ALL	1.50	V-0	80	80	80	-	-	-	-	-	-	-	-
PBT	Later 4 G/15 (q) (r)	ALL	0.75 1.50 3.00	HB HB HB	140 140 140	130 130 140	140 140 140	4 2 0	0 0 0	- - 0	- - 5	- - 2	- - -	- - -	- - -
	Later 4 G/(l) (q) (r) (see notes)	ALL	0.75 1.50 3.00	HB HB HB	130 130 130	130 130 140	140 140 140	4 2 0	0 0 0	- - 1	- - 6	- - 2	- - -	- - -	- - -
	Later 4 G/30 (q) (r)	ALL	0.75 1.50 3.00	HB HB HB	130 130 130	130 130 140	140 140 140	3 1 0	0 0 0	- - 1	- - 6	- - 1	- - -	- - -	- - -
	Later 4 CE/50 (q) (r)	NC	0.71	HB	75	75	75	-	-	-	-	-	-	-	-
	Later 4-V0 (q) (r)	ALL	0.75 1.50 3.00	V-0 V-0 V-0	140 140 140	130 130 140	140 140 140	4 3 2	0 0 0	- - 4	- - 6	- - 2	- - -	- - -	- - -
	Later 4 G/10-V0 (q) (r)	ALL	0.75 1.50 3.00	V-0 V-0 V-0	130 130 130	120 120 130	120 120 130	4 3 2	0 0 0	- - 4	- - 6	- - 2	- - -	- - -	- - -
	Later 4 G/(l)-V0 (q) (r) (see notes)	ALL	0.75 1.50 3.00	V-0 V-0 V-0	130 130 130	120 120 130	120 120 130	4 3 2	0 0 0	- - 4	- - 6	- - 2	- - -	- - -	- - -
	Later 4 G/30-V0 (q) (r)	ALL	0.75 1.50 3.00	V-0 V-0 V-0	140 140 140	130 130 140	130 130 140	3 2 0	0 0 0	- - 4	- - 6	- - 2	- - -	- - -	- - -
	Later 4 G/30-V0CT1 (q) (r)	NC	0.75 1.50 3.00	V-0 V-0 V-0	75 75 75	75 75 75	75 75 75	- - -	- - -	- - -	- - 5	- - 1	- - -	- - -	- - -
	Later 4 G/30-V0CT2 (q) (r)	NC	0.75 3.00	V-0 V-0	75 75	75 75	75 75	- -	- -	- -	- 5	- 1	- -	- -	- -
	Later 4E61 GCER/450-V0 (q) (r)	GY	0.75 1.50 3.00	V-0 V-0 V-0	75 75 75	75 75 75	75 75 75	3 2 1	0 0 0	- - 0	- - 4	- - 1	- - -	- - -	- - -
POM	Latan 9 (q) (r)	NC	1.50	HB	50	50	50	-	-	-	-	-	-	-	-
	Latan 13 S/30 (q) (r)	ALL	1.50	HB	50	50	50	-	-	-	-	-	-	-	-
PPS	Larton G/40 (q) (r)	NC,BK	0.42 0.75 1.50 3.00	V-0 V-0 V-0 V-0	130 130 130 130	130 130 130 130	130 130 130 130	- 5 4 0	- 0 0 0	- - - -	- - - -	- - - -	- - - -	- - - -	- - - -
	Larton GCE/600 (q) (r)	NC,BK	0.75 1.50 3.00	V-0 V-0 V-0	130 130 130	130 130 130	130 130 130	3 3 0	1 1 1	- - -	- - -	- - -	- - -	- - -	- - -
	Larton GCE/650 (q) (r)	ALL	0.75 1.50 3.00	V-0 V-0 V-0	130 130 130	130 130 130	130 130 130	3 0 0	3 0 0	- - -	- - -	- - -	- - -	- - -	- - -
	Larton L G/40 (q) (r)	NC	0.75	V-0	130	130	130	-	-	-	-	-	-	-	-
PSU	Lasulf (q) (r)	ALL	1.50	HB	50	50	50	-	-	-	-	-	-	-	-
SPS	Laestra E01 G/30 (q) (r)	ALL	1.50	HB	50	50	50	-	-	-	-	-	-	-	-
	Laestra G/30 - V0CT1 (q) (r)	ALL	0.75 1.50 3.00	V-0 V-0 V-0	130 130 130	120 120 120	130 130 130	3 2 0	0 0 0	- - 3	- - 6	- - 1	- - -	- - -	- - -
	Laestra G/22 - V0 (q) (r) (u)	ALL	1.00 1.50 2.00 3.00	- V-0 V-0 V-0	50 125 125 125	50 120 120 120	50 120 120 120	- 1 - 0	- 0 - 0	- - - 0	- - - 5	- - - 1	- - - 800	- - 825	- - 850
	Laestra G/30 - V0 (q) (r) (u)	ALL	1.00 1.50 2.00 3.00	- V-0 V-0 V-0	50 125 125 125	50 120 120 120	50 120 120 120	- 1 - 0	- 0 - 0	- - - 0	- - - 6	- - - 2	- - - 800	- - 825	- - 850
	Laestra h G/30 - V0 (q) (r)	ALL	1.00 1.50 2.00 3.00	- V-0 V-0 V-0	50 125 125 125	50 120 120 120	50 120 120 120	- 1 - 0	- 0 - 0	- - - 0	- - - 5	- - - 2	- - - 825	- - 850	- - 850
	Laestra G/40 (q) (r)	@ @ BK BK	1.50 3.00 1.50 3.00	- - - -	105 105 105 110	105 105 105 110	105 105 105 110	0 1 0 1	0 0 0 0	- - - -	- - - -	- - - -	- - - -	- - - -	- - - -

Product Material	Colors	Min Thk mm	UL 94 Flame Class	R.T.I.											
				Elec				Mech							
				With Imp	w/o Imp	H W	H A	H V	D 4	C T	G W	G W			
<b>SPECIALS</b>															
PA6	Latilub 62-01M G/30 (q) (r)	NC, (BK)	0.86	HB	65	65	65	-	-	-	-	-	-	-	-
PA66	Latilub 66-20T G/20 (q) (r)	ALL	0.75	HB	120	100	110	3	0	-	-	-	-	-	-
			3.00	HB	120	100	115	0	0	0	6	0	-	-	
	Latilub 66-01M (q) (r)	NC	0.72	HB	65	65	65	-	-	-	-	-	-	-	-
	Latilub 66-01M G/(a) (q) (r) (see notes)	NC	0.72	HB	65	65	65	-	-	-	-	-	-	-	-
	Latilub 66-01M G/30 (q) (r)	NC	0.72	HB	65	65	65	-	-	-	-	-	-	-	-
PA12	Latamid 12 H FE90:0081 (q) (r)	NC,(BK)	0.71-3.0	HB	65	65	65	-	-	-	-	-	-	-	-
PC	Latilub 87/28-20T (q) (r)	NC,BK	1.50	HB	80	80	80	-	-	-	-	-	-	-	-
			3.00	V-1	80	80	80	-	-	-	-	-	-	-	
			6.00	V-0	80	80	80	-	-	-	-	-	-	-	
	Latilub 87/24UV-20T (q) (r)	GY	0.75	HB	80	80	80	-	-	-	-	-	-	-	-
	Latilub 87/28-12T G/20 (q) (r)	NC,BK	1.40	HB	80	80	80	-	-	-	-	-	-	-	-
			3.00	V-1	80	80	80	-	-	-	-	-	-	-	
			6.00	V-0	80	80	80	-	-	-	-	-	-	-	-
POM	Latilub 73/13-20T (q) (r)	NC,BK	1.50	HB	50	50	50	-	-	-	-	-	-	-	-
	Latilub 73/13-15T G/15 (q) (r)	NC	1.50	HB	50	50	50	-	-	-	-	-	-	-	-
			3.00	HB	50	50	50	-	-	-	-	-	-	-	
PPS	Latilub 80-15T G/30 (q) (r)	NC,BK	0.74	V-0	130	130	130	-	-	-	-	-	-	-	-
PA/PP	Latiblend 6252 H2 G/30 (q) (r)	ALL	0.75	HB	50	50	50	-	-	-	-	-	-	-	-
PA6	Latiohm 63-08 PD02 G/25 (q) (r)	BK	0.75	HB	65	65	65	-	-	-	-	-	-	-	-
		BK	3.00	HB	65	65	65	-	-	-	-	-	-	-	
<b>DISCLAIMER:</b>															
LATI do not guarantee that the data contained in this list are current, complete and error-free.															
To double check the values, users are kindly requested to contact our technical or commercial offices.															
LATI Industria Termoplastici S.p.A. declines all responsibility arising from any improper use of the information described in this document.															
<i>Copyright © 1999 LATI S.p.A. - All Rights Reserved</i>															

 <b>Status of U.L. Approvals</b> <b>System Components, Electrical Insulation - Component</b>			
<i>file LATI: E 211801 - OBJSz</i>			
System Component	System Dsg	System Temp Class	System Max V
Latamid 6 H2 G/20-V2 HF	LATIS 1	155 (F)	600 V
Latamid 66 H2 G/25-V0 CT1	LATIS 1	155 (F)	600 V
Latamid 66 H2 G/25-V0 KB1	LATIS 1	155 (F)	600 V
Latamid 66 H2 G/30	LATIS 1	155 (F)	600 V
Latamid 68 H2-V0	LATIS 1	155 (F)	600 V
Later 4 G/30-V0	LATIS 1	155 (F)	600 V
<b>DISCLAIMER:</b>			
LATI do not guarantee that the data contained in this list are current, complete and error-free.			
To double check the values, users are kindly requested to contact our technical or commercial offices.			
LATI Industria Termoplastici S.p.A. declines all responsibility arising from any improper use of the information described in this document.			
<i>Copyright © 1999 LATI S.p.A. - All Rights Reserved</i>			